

USA Type Quick Coupler

ARO TYPE

FEATURES

- Accepts 1/4 ARO Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40°F ~225°F (-20℃~107℃)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop

★ ONE TOUCH TYPE (PU11 Series)



Model	Size
PU11-2SF	1/4" NPT FEMALE THREAD
PU11-3SF	3/8" NPT FEMALE THREAD



Model	Size
PU11-2PF	1/4" NPT FEMALE THREAD
PU11-3PF	3/8" NPT FEMALE THREAD



Model	Size
PU11-2SH	1/4" HOSE BARB
PU11-3SH	3/8" HOSE BARB



Model	Size
PU11-2PH	1/4" HOSE BARB
PU11-3PH	3/8" HOSE BARB



Model	Size
PU11-2SM	1/4" NPT MALE THREAD
PU11-3SM	3/8" NPT MALE THREAD



Model	Size
PU11-2PM	1/4" NPT MALE THREAD
PU11-3PM	3/8" NPT MALE THREAD



Model	Size
PU6-2SF	1/4" NPT FEMALE THREAD
PU6-2SF	3/8" NPT FEMALE THREAD



Model	Size
PU6-2PF	1/4" NPT FEMALE THREAD
PU6-3PF	3/8" NPT FEMALE THREAD



Model	Size
PU6-2SH	1/4" HOSE BARB
PU6-3SH	3/8" HOSE BARB



Model	Size
PU6-2PH	1/4" HOSE BARB
PU6-3PH	3/8" HOSE BARB



Model	Size
PU6-2SM	1/4" NPT MALE THREAD
PU6-3SM	3/8" NPT MALE THREAD



Model	Size
PU6-2PM	1/4" NPT MALE THREAD
PU6-3PM	3/8" NPT MALE THREAD

★ TWO TOUCH TYPE (PU6 Series)

Europe Type Quick Coupler

UNIVERSAL TYPE

FEATURES

- Accepts 1/4 UNIVERSAL Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40°F ~225°F (-20℃~107℃)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop



P/N	Size
PE1-2SF	1/4" BSP
PE1-3SF	3/8" BSP
PE1-4SF	1/2" BSP



P/N	Size
PE1-2PF	1/4" BSP
PE1-3PF	3/8" BSP
PE1-4PF	1/2" BSP



Model	Size
PE1-2SR	Φ6×12
PE1-3SR	Φ8×15



Model	Size
PE1-2PR	Φ6×12
PE1-3PR	Φ8×15



P/N	Size
PE1-2SH	Φ6.35
PE1-3SH	Φ8
PE1-4SH	Φ10



P/N	Size
PE1-2PH	Φ6.35
PE1-3PH	Φ8
PE1-4PH	Φ10



P/N	Size
PE1-1SP	Φ4×6
PE1-2SP	Φ5×8
PE1-3SP	Φ6.5×10
PE1-4SP	Φ8×12



P/N	Size
PE1-1PP	Φ4×6
PE1-2PP	Φ5×8
PE1-3PP	Φ6.5×10
PE1-4PP	Φ8×12



P/N	Size
PE1-2SM	1/4" BSP
PE1-3SM	3/8" BSP
PE1-4SM	1/2" BSP



P/N	Size
PE1-2PM	1/4" BSP
PE1-3PM	3/8" BSP
PE1-4PM	1/2" BSP

Europe Type Quick Coupler

UNIVERSAL TYPE

FEATURES

- Accepts 1/4 UNIVERSAL Type plugs
- Heavy-duty,high-quality design
- Deep knurled socket sleeve for positive gripping
- Proven and positive connection using ball-locjing mechanism

SPECIFICATIONS

- Maximum Working Pressure: 150 PSI
- Temperature Range: -40 °F ~225 °F (-20 °C~107°C)
- Air Flow: 35 SCFM at 100 PSIG inlet with 10 PSIG pressure drop



P/N	Size
PE2-2SF	1/4" BSP
PE2-3SF	3/8" BSP
PE2-4SF	1/2" BSP



P/N	Size
PE2-2PF	1/4" BSP
PE2-3PF	3/8" BSP
PE2-4PF	1/2" BSP



P/N	Size
PE2-2SR	Φ6×12
PE2-3SR	Φ8×15



P/N	Size
PE2-2PR	Φ6×12
PE2-3PR	Φ8×15



P/N	Size
PE2-2SH	Φ6.35
PE2-3SH	Φ8
PE2-4SH	Φ10



P/N	Size
PE2-2PH	Φ6.35
PE2-3PH	Φ8
PE2-4PH	Φ10



P/N	Size
PE2-1SP	Φ4×6
PE2-2SP	Φ5×8
PE2-3SP	Φ6.5×10
PE2-4SP	Φ8×12



P/N	Size
PE2-1PP	Φ4×6
PE2-2PP	Φ5×8
PE2-3PP	Φ6.5×10
PE2-4PP	Φ8×12



P/N	Size
PE2-2SM	1/4" BSP
PE2-3SM	3/8" BSP
PE2-4SM	1/2" BSP



P/N	Size
PE2-2PM	1/4" BSP
PE2-3PM	3/8" BSP
PE2-4PM	1/2" BSP